HITACHI
Inspire the Next

CP-X265 series

Screen Size 4.3		Throw distance	
Diagonal*	Width*	Min*	Max*
30	24	34	41
60	48	70	84
80	64	93	112
100	80	117	140
120	96	140	169
150	120	176	211
200	160	234	282
300	240	352	423

Throw ratio: 1.5 - 1.7:1 (distance:width)
*Measured in inches

- 2,500 ANSI Lumens
- Native XGA Resolution
- 7.2 lbs
- 2 RGB inputs and 1 RGB Output
- Component / Composite / S-Video Inputs
- HDTV Theater Ready
- Transition Detector
- Digital Gamma Correction
- Auto Vertical Keystone Correction
- Remote Control with "My Buttons"
- Network Control, Maintenance & Scheduling
- 34 dB (Whisper Mode)
- Supplied Soft Case
- My Screen / My Memory
- Whiteboard Mode
- Blackboard Mode
- Approx. 3,000 hrs (Whisper Mode)
- Security Bar
- Kensington Security Slot
- Progressive Scan
- Audio Input / Output
- Input Source Naming
- RJ-45 Port
- 500:1 Contrast ratio

SPECIFICATIONS

Model name			CP-X265
Liquid crystal panel structure			0.63" polysilicon active-matrix TFT x 3
Number of pixels			786,432 pixels
Resolution		Video	540 TV lines
		RGB	1024 dots X 768 lines
Colors			16.7 million colors
Aspect ratio			Native 4:3/16:9 compatible
Lens			F1.7 - 1.9 manual zoom 1:1.2
Throw ratio (distance:width)			1.5 - 1.7:1
Lamp			200W UHB
Brightness			2,500 ANSI lumens
Expected lamp life			Approx. 3,000 hrs (Whisper Mode) Approx. 2,000 hrs (Natural Mode)
Contrast ratio			500:1
Speakers			1W x 1
Power supply			AC100-120V/AC220-240V 50/60Hz
Power consumption			330W
Operating temperature			5°C ~ 35°C (41°F ~ 95°F)
Input signals		RGB	VGA, SVGA, XGA,SXGA, SXGA+, UXGA, MAC13", MAC16"
		Composite video	NTSC, NTSC4.43, PAL, SECAM, PAL-M, PAL-N
		Component video	480i, 576i, 480p, 720p, 1080i
Acoustic noise level			39dB (34dB in whisper mode)
H sync			15kHz ~ 106kHz
V sync			50Hz ~ 120Hz
Vertical keystone correction			Digital keystone +/– 30°
Approvals			UL60950 / C-UL, FCC Part15, Class B, CE, EN60950
Input/Output terminals	RGB input	Analog RGB	15-pin D-sub connector x 2
	RGB output	RGB	15-pin D-sub connector x 1
	Video input	S-video	Mini DIN 4-pin connector x 1
		Composite video	RCA jack x 1
		Component video	RCA jack x 3
	Audio	Input	Stereo mini jack x 2, RCA jack (L/R) x 1
		Output	Stereo mini jack x 1
	Control terminals		9-pin D-sub connector x 1 (RS-232 control) USB connector (USB mouse) x 1
	Ethernet		RJ-45 Port / 100BASE-T
Chassis	Dimensions		12.0" x 4.2" x 9.8" (W x H x D)
	Weight		7.2 lbs.
	Supplied accessories		Remote Control, Batteries (AA), RGB Cable, RCA Video Cable, Power Cord, Multiple Language Operator / Safety Manual, Soft Case, Security Label
Replacement parts	Lamp		CPX260LAMP
	Remote Control		HL02221
	Filter		NJ22222

www.hitachi.us/digitalmedia